



7600 SERIES LOW PRESSURE REEL

7600 OLP spring retractable hose reels are very robust and ideal for the most demanding applications. The reel's base and guide arm are formed from high-grade steel and engineered with structural forms and gussets to yield the greatest amount of strength. The basic reel without hose can be used for air, water or oil. Consult your mdi representative for compatible products and hoses. Guide arm adjusts to 7 positions.

SPECIFICATIONS:

Hose I.D. (in)	3/8"
Hose O.D. (in)	.600
Hose Length (m)	15
Pressure (psi)	500
Inlet (in)	1/2 NPT(F)
Reel Outlet (in)	1/2 NPT(F)
Hose Included	No
Max Temperature (°C)	66
Seal Type	Buna N
Swivel Material	Steel
Shaft Material	Steel
Dimensions	620x620x300
Weight	22 Kg



FEATURES & BENEFITS:

- Reinforced steel - The steel guide arm and base are stamped with ribs and gussets to insure maximum strength and lightest possible weight.
- Full flow stress free swivel design - The full flow swivel combines the highest grade seal design and materials with bearing areas to insure maximum service life. The hose is plumbed into the base to eliminate the risk of undue stress on the swivel.
- Long life drive spring - Declutching arbor virtually eliminates possibility of spring damage due to reverse winding. Only the highest quality spring steel is used and conditioned to insure there are no imperfections offering maximum service life.
- Quality finish and corrosion resistant - Individually powder coated components offer the maximum protection from premature corrosion.

PART NO.

AF-R-7600 OLP

7600 Series Low Pressure Reel - Bare: 15m X 3/8" Hose Capacity