



FILL-RITE 12/24V DC 76 LPM PUMP

You work through all kinds of conditions, so why shouldn't your fuel transfer pump? For over 60 years, Fill-Rite has set the standard for reliable fuel transfer pumps, meters, and accessories. Our customers recognise Fill-Rite for its durability and years of elite performance in the field. Proudly made in the USA with global materials, Fill-Rite equipment is constructed with heavy-duty materials to withstand rugged everyday use, extreme weather exposure, and both on and off-road applications. Fill-Rite is supported by a wide network of distributors and retailers, ensuring you will always be able to find replacement parts and rebuild kits for your fuel transfer equipment.

FEATURES & BENEFITS:

- Cast-Iron Construction heavy-duty, cast-iron construction provides unmatched durability, withstanding the harshest conditions out in the field or at the job site
- Reliable Performance Fill-Rite's trusted rotary vane pump technology delivers 75L per minute, perfect for filling equipment with fuel tanks from 75-302L
- Mobile Tanks powered by a 12V motor and equipped with a 50.8mm bung mount, this pump is ideal for wiring to 12 volt batteries and installing onto transfer tanks in truck beds
- Fluid Compatibility designed for daily use with gasoline, diesel, ethanol blends up to E15, biodiesel blends up B20, kerosene, and mineral spirits
- Easy Installation adjustable electrical junction box rotates 180 for easier wiring and more flexible installations in tight spaces
- Long Life thermally-protected motor prevents overheating, ensuring your pump performs for years worry free
- Equipment Safeguard built-in mesh strainer filters out particulates in your fuel, preventing damage to your equipment
- Reliable On-Off Switch on-off switch lever features a robust metal stopping arm, preventing premature failure from repeated use
- Limited Lifetime Warranty we stand behind our product with an industry-leading Limited Lifetime Warranty, protecting your investment



SPECIFICATIONS:

Max Flowrate	75 LPM
Power Type	12V or 24V DC Available
Inlet Size / Connection / Thread	25.4mm / Female / NPT
Outlet Size / Connection / Thread	25.4mm / Female / NPT
Mounting Size / Thread / Type	50.8mm / NPT / Bung Mount
Duty Cycle (min)	30min on / 30min off
Power Source	Electrical
Motor Power (HP)	0.25
Max Current (A)	19 A
Thermal Protection Switch	Yes
Self Priming	Yes
Suction Lift (mm)	2438.4
Dry Vacuum (mm Hg)	127
Discharge Head (mm)	11277.6
Strainer Mesh Size (Micron)	20x20
Max Operating Pressure (PSI)	16
Viscosity Range (cSt)	1 to 4

PART NO.		WEIGHT	DIMENSIONS
AF-FR-4211DLA	FILL-RITE 12V DC 76 LPM Pump Kit, 3.6m Hose, 900 Series Meter and Auto Shut Off Nozzle	17 Kg	26x56x50
AF-FR-4411DLA	FILL-RITE 24V DC 76 LPM Pump Kit, 3.6m Hose, 900 Series Meter and Auto Shut Off Nozzle	17 Kg	26x56x50