



FLUIDLINK MICRO FUEL MANAGEMENT SYSTEM

The FLUIDLINK MICRO Controller is a single hose/pump fluid management solution. It utilises our intuitive cloudbased FLUIDLINK management software. Using the inbuilt stainless-steel keypad and RFID reader and add on optional card readers and Bluetooth readers, the user can choose between a large range of access IDs and can configure the system with a vast range of security profiles to ensure all required fuel tracking and security is logged and managed.

Surface/Tank Mount: designed to be installed on the surface of a tank or wall or on a pedestal.

FEATURES & BENEFITS:

- Full stainless steel construction
- Backlit stainless steel keypad
- Monochrome Graphics Display with white backlight
- Built-in RFID reader
- Multiple mounting options
- Single pump support, non-expandable
- Real-time (online) intuitive management software
- Seamless integration with most existing & new pumping equipment
- Multiple ID types can be used on a single system, pins, RFID, fuel cards, Bluetooth tags, and manual entry of asset numbers
- Dual tank ATG (auto dip) compatible as standard, just add sensors
- Up to 8000 users per system
- Up to 100 security profiles (how users access fuel) per enterprise
- 80K transaction memory buffer, never lose a transaction
- Battery-backed, never lose part transactions on power failure
- 4G, CAT-M1 & LAN communication options provide optimum coverage range



FLUIDLINK MICRO - SOLAR SPECIFICATIONS:

- Solar Complete with Antenna and 20 Fob Keys & 1 x Brackets (FL-570271) comes with a 7.8AHr 12VDC battery and a solar charge controller for direct connection to a solar panel including SIM & 3-Year Pro Web Reporting Access.
- Solar Supply: Includes a 7.8AHr 12VDC Battery

FLUIDLINK MICRO - 240V SPECIFICATIONS:

- 240V Complete with Antenna and 20 Fob Keys & 1 x Brackets (FL-570271) Includes SIM & 3-Year Pro Web Reporting Access.
- Power Supply: 240v

FLUIDLINK MICRO - 12-24V SPECIFICATIONS:

- 12-24V Complete with Antenna and 20 Fob Keys & 1 x Brackets (FL-570271) including SIM & 3-Year Pro Web Reporting Access.
- 12-24VDC Supply: Suitable for use when you have an existing 12VDC or 24VDC power supply in place or want to run the system on extra low voltage from a vehicle or for safety reasons. Allow 700mA for the Micro controller on its own or 1.5 Amps if running a solenoid valve as well as the Micro controller.

PART NO.

AF-FL-826904	FLUIDLINK MICRO Surface/Tank Mount FMS - Solar
AF-FL-826905	FLUIDLINK MICRO Surface/Tank Mount FMS - 240V
AF-FL-826906	FLUIDLINK MICRO Surface/Tank Mount FMS - 12-24V