



# FARM REFUELLERS

## SINGLE SKIN DIESEL STORAGE TANK



### FEATURES & BENEFITS:

- Complete with 2" fill point camlock ball valve, check valve and Calibrated dipstick
- Lifting lugs on tank
- Heavy duty front step fitted to front of the tank for access to dip point
- Designed to provide a cost effective solution to replace overhead diesel tanks in the agricultural industry

### APPLICATIONS:

- Agriculture

### SPECIFICATIONS

PART NO.	MAX CAPACITY (L)	SAFE FILL LEVEL (L)	DIMENSIONS (MM)	TARE WEIGHT (KG)
AF-FRT-4.5	4,830	4,500	2,895 (L) x 1,800 (W) x 2,005 (H)	668
AF-FRT-8.5	8,948	8,500	3,669 (L) x 2,050 (W) x 2,255 (H)	850

\* GA drawings available on request

### PUMPING OPTIONS

- 12V Bi Pump Kit 80 LPM with 4m Hose, Mechanical Meter, Auto Nozzle and 10 Micron Bulk Fuel Filter with Breather
- 240V Bowser 70 LPM with 4m Hose, Mechanical Meter, Auto Nozzle and 10 Micron Bulk Fuel Filter with Breather
- 240V Fuel Management Bowser 70 LPM with 4m Hose, Software Kit, USB Key Reader, Managers Key, 10 User Keys, Auto Nozzle and 10 Micron Bulk Fuel Filter with Breather