



GRACO HUSKY 1050 AIR-OPERATED DOUBLE DIAPHRAGM PUMP

Husky 1050 PP (NPT) Pump, Centre Flange, PP Centre Section, PP Seats, PTFE Balls & PTFE Diaphragm

The Husky 1050 air-operated diaphragm pump features a stall-free low pulsation air valve which provides a smooth and rapid changeover.

The one-piece centre section eliminates leaks and reduces maintenance on Husky pumps when compared to other diaphragm pumps.



SPECIFICATIONS:

Air Exhaust Port Size (in)	3/8
Air Exhaust Port Thread Gender	Female
Air Inlet Size (in)	1/4
Air Inlet Thread Gender	Female
Fluid Inlet Size (cm / in)	2.54 / 1
Fluid Outlet Size (cm / in)	2.54 / 1
Maximum Air Consumption (SCFM)	67
Maximum Air Pressure (bar / psi)	8.6 / 125
Maximum Cycle Rate (CPM)	280
Maximum Flow Rate (L/min)	189
Maximum Fluid Pressure (bar / psi)	8.6 / 125
Maximum Operating Temperature (°C)	66
Maximum Solid Size (mm)	3.175
Diaphragm Compatible Material	PTFE

FEATURES & BENEFITS:

- Longer Diaphragm Life: Up to 5x longer diaphragm life for less maintenance and down-time
- Modular Air Valve: Stall-free, low pulsation operation provides smooth and rapid changeover
- One-Piece Center Section: Eliminates air leaks for more efficient operation
- Four-Bolt Joint Design: Bolted design provides even sealing pressure for leak-free operation
- Multiple Ports: Increased number of ports for installation flexibility
- Spring loaded, externally serviceable pilot valves for faster change over and reduced pulsation
- 30% more efficient than the market leader
- 20% increase in fluid flow compared to the Husky 1040
- Suitable for highest Chemical Resistance where PTFE is required

PART NO.		WEIGHT	DIMENSIONS
AF-G-649006	GRACO Husky 1050 PP 1" AODD	10 Kg	500x300x500



GRACO HUSKY 1050 AIR-OPERATED DOUBLE DIAPHRAGM PUMP

Husky 1050 PP (NPT) Pump, End Flange, PP Centre Section, PP Seats, PTFE Balls & PTFE Diaphragm

The Husky 1050 air-operated diaphragm pump features a stall-free low pulsation air valve which provides a smooth and rapid changeover. The one-piece centre section eliminates leaks and reduces maintenance on Husky pumps when compared to other diaphragm pumps.



SPECIFICATIONS:

Air Exhaust Port Size (in)	3/4
Air Exhaust Port Thread Gender	Female
Air Inlet Size (in)	1/2
Air Inlet Thread Gender	Female
Fluid Inlet Size (cm / in)	2.54 / 1
Fluid Outlet Size (cm / in)	2.54 / 1
Maximum Air Consumption (SCFM)	67
Maximum Air Pressure (bar / psi)	8.6 / 125
Maximum Cycle Rate (CPM)	280
Maximum Flow Rate (L/min)	189
Maximum Fluid Pressure (bar / psi)	8.6 / 125
Maximum Operating Temperature (°C)	66
Maximum Solid Size (mm)	3.175
Diaphragm Compatible Material	PTFE

FEATURES & BENEFITS:

- Longer Diaphragm Life: Up to 5x longer diaphragm life for less maintenance and down-time
- Modular Air Valve: Stall-free, low pulsation operation provides smooth and rapid changeover
- One-Piece Center Section: Eliminates air leaks for more efficient operation
- Four-Bolt Joint Design: Bolted design provides even sealing pressure for leak-free operation
- Multiple Ports: Increased number of ports for installation flexibility
- Spring loaded, externally serviceable pilot valves for faster change over and reduced pulsation
- 30% more efficient than the market leader
- 20% increase in fluid flow compared to the Husky 1040
- Suitable for highest Chemical Resistance where PTFE is required

PART NO.		WEIGHT	DIMENSIONS
AF-G-649034	Graco 1" 1050 Poly AODD NPT Ports	10 Kg	490x430x220