



GRACO HUSKY 2150 SERIES 2" ALUMINIUM DIAPHRAGM PUMP



The Husky 2150 air operated diaphragm pump features a stall-free low pulsation air valve which provides a smooth and rapid changeover.

FEATURES & BENEFITS:

- Overall improved efficiency (up to 40% more efficient)
- Highest fluid flow rate in its class
- Up to five times longer diaphragm life compared to other air operated diaphragm pumps
- Expanded material offering to handle endless applications
- Fewer parts than industry peers, the air valve is externally accessible so it can be serviced quickly and easily without uninstalling the diaphragm pump
- 51 mm (2 in.) ANSI end-porting
- Fluid flow up to 568 lpm (150 gpm)
- Fluid pressure to 8.4 bar, 0.84 MPa (120 psi)
- Lube-free operation
- Epoxy-coated air section for tough environmental conditions



SPECIFICATIONS:

Air Exhaust Port Size (in)	3/4
Air Exhaust Port Thread Gender	Female
Air Exhaust Port Thread Type	NPT
Air Inlet Size (in)	1/2
Air Inlet Thread Gender	Female
Air Inlet Thread Type	NPT
Application	Industrial
Centre Section Material	Aluminium
Fluid Inlet Size (in / mm)	2 / 50.8
Fluid Inlet Thread Gender	Female
Fluid Outlet Size (in / mm)	2 / 50.8

Fluid Outlet Thread Gender	Female
Fluid Section Material	Aluminium
Manifold Configuration	End Port
Material	Aluminium
Maximum Air Pressure (bar / psi)	8 / 120
Maximum Cycle Rate (CPM)	145
Maximum Flow Rate (L/min)	568
Maximum Operating Temperature (°C)	93
Maximum Solid Size (mm)	6.35
Dimensions (cm)	92x71x36
Type	Pneumatic diaphragm pump selector

MODELS		PUMP	SEAT MATERIAL	BALL MATERIAL	DIAPHRAGM MATERIAL	WEIGHT
AF-G-DF3525	Suitable for Oil and Unleaded Fuel	NPT	TPE	Acetal	TPE	27 Kg
AF-G-DF525	Suitable for Oil and Unleaded Fuel	BSP	TPE	Acetal	TPE	29 Kg
AF-G-DF3GGG	Suitable for Waste Oil and Diesel	NPT	Geolast	Geolast	Geolast	28 Kg
AF-G-DFCGGG	Suitable for Waste Oil and Diesel	BSP	Geolast	Geolast	Geolast	28 Kg