



GRACO HUSKY 515 ADBLUE PUMP

The Husky 515 air-operated double diaphragm pump features a stall-free low pulsation air valve which provides a smooth and rapid changeover.

The bolt through fluid cover design eliminates leaks and makes the Husky safer with higher reliability.

FEATURES & BENEFITS:

- Centre and end porting options.
- No mechanical seals to cause fluid leaks or failures
- Runs quietly at less than 85 dBA with easy-to-use remote muffler capability for even lower noise levels
- Easy-to-service air valve and ball checks
- Operates on as little as 1.4 bar (0.14 MPa, 20 psi)
- Split manifold option to pump multiple fluids without mixing
- Delivery up to 56.7 lpm (15 gpm)
- Easy-to-service air valve and ball checks
- Reliable air valve for years of dependable performance



SPECIFICATIONS:

Air Exhaust Port Size (in)	3/8
Air Exhaust Port Thread Gender	Female
Air Exhaust Port Thread Type	NPT
Air Inlet Size (in)	1/4
Air Inlet Thread Gender	Female
Air Inlet Thread Type	NPT
Ball Material	PTFE
Centre Section Material	Polypropylene
Compressor Required	Yes
Diaphragm Compatible Material	PTFE
Diaphragm Material	PTFE/EPDM 2-Piece
Fluid Inlet Size (in / mm)	1/2 / 12.7
Fluid Inlet Thread Gender	Female
Fluid Inlet Thread Type	BSPT
Fluid Outlet Size (in / mm)	1/2 / 12.7

Fluid Outlet Thread Gender	Female
Fluid Outlet Thread Type	BSPT
Fluid Section Material	Polypropylene
Manifold Configuration	Centre Port
Manifold O-Ring Material	PTFE
Diaphragm Compatible Material	PTFE
Diaphragm Material	PTFE/EPDM 2-Piece
Maximum Air Pressure (bar / psi)	7 / 100
Maximum Cycle Rate (cpm)	400
Maximum Flow Rate (l/min)	57
Maximum Fluid Pressure (bar / psi)	7 / 100
Maximum Operating Temperature (°C)	66
Maximum Solid Size (cm / mm)	0.2383 / 2.4
Minimum Operating Temperature (°C)	4
Power Source	Air

PART NO.		WEIGHT	DIMENSIONS
AF-G-D5B911	GRACO Husky 515 1/2" BSP PP AdBlue Pump - PTFE	4 Kg	23x32x28