



# GRACO HUSKY 515 BSP DIAPHRAGM PUMP - ACETAL/BUNA

The Husky 515 air-operated double diaphragm pump features a stall-free low pulsation air valve which provides a smooth and rapid changeover.

The bolt through fluid cover design eliminates leaks and makes the Husky safer with higher reliability.

## FEATURES & BENEFITS:

- Center and end porting options.
- No mechanical seals to cause fluid leaks or failures
- Runs quietly at less than 85 dBA with easy-to-use remote muffler capability for even lower noise levels
- Easy-to-service air valve and ball checks
- Operates on as little as 20 psi (1.4 bar, 0.14 MPa)
- Split manifold option to pump multiple fluids without mixing
- Delivery up to 15 gpm (56.7 lpm)
- Easy-to-service air valve and ball checks
- Reliable air valve for years of dependable performance
- Diaphragm compatible material: Buna
- Compressor Required: Yes



## SPECIFICATIONS:

Air Exhaust Port Size (in)	3/8	Maximum Air Pressure (bar/psi)	7 / 100
Air Exhaust Port Thread Gender	Female	Maximum Cycle Rate (CPM)	400
Air Inlet Size (in)	1/4	Maximum Flow Rate (L/min)	57
Air Inlet Thread Gender	Female	Maximum Fluid Pressure (bar/psi)	7 / 100
Fluid Inlet Size (mm/in)	12.7 / 1/2	Maximum Operating Temperature ( C/ F)	82 / 180
Fluid Inlet Thread Gender	Female	Maximum Solid Size (mm/in)	2.4 / 0.09375
Fluid Outlet Size (mm/in)	12.7 / 1/2	Minimum Operating Temperature ( C/ F)	4 / 40
Fluid Outlet Thread Gender	Female	Maximum Fluid Pressure (MPa)	0.7
Maximum Air Consumption (SCFM)	28	Maximum Air Pressure (MPa)	0.7

PART NO.		DIMENSIONS	WEIGHT
AF-G-D5A277	GRACO Husky 515 1/2" BSP Diaphragm Pump - Acetal/Buna	28x31x22	5 Kg