



GRACO LDX SERIES AIR/WATER REEL

Graco's entry-level, industrial-grade LDX hose reel offers incredible value for cost-conscious workshops. Its all-metal frame and specially crafted, long-lasting components provide consistent release and retraction.

Designed for smaller garages, independent repair facilities and industrial manufacturing environments.

SPECIFICATIONS:

Application	Air, Water, Antifreeze, WWS
Frame Type	Dual Pedestal
Hose Inside Diameter (in / mm)	3/8 / 9.525
Hose Length (m)	15
Hose Reel Type	Reel with Hose
Inlet (in / mm)	3/8 / 9.525
Inlet Thread Gender	Male
Inlet Thread Type	NPT
Maximum Temperature (°C)	65
Minimum Temperature (°C)	-26
Mount Location	Truck Mount, Bench Mount
Outlet (in / mm)	3/8 / 9.525
Outlet Thread Gender	Male
Outlet Thread Type	NPT
Type	Spring-Rewind Reel
Wetted Parts	Hybrid Polymer, Brass, Nitrile Rubber
Dimensions	53x59x28
Weight	21 Kg



FEATURES & BENEFITS:

- Dual Pedestal Frame – Ribbed metal for increased stability and robustness.
- External Swivel Housing – Quickly access swivel seal for faster repairs.
- Ball Bearing Swivel – Swivel designed with internal ball bearings reduces friction and ensures smooth operation.
- Adjustable Arm – Easily change to one of six arm positions to fit your application.
- Large Hose Capacity with Small Profile - Compact design accommodates up to a 15 metre (50 foot) hose to meet a wide variety of application requirements.

PART NO.

AF-G-HEL010

GRACO LDX Series Air/Water NPT Reel - 15m x 3/8" ID Hose



GRACO LDX SERIES AIR/WATER REEL

DIMENSIONS:

A	89 mm / 3.5 inches
B *	191 mm / 7.5 inches
C	125 mm / 4.9 inches
D	221 mm / 8.7 inches
E •	483 mm / 19 inches
F	239 mm / 9.4 inches
G ¶	445 mm / 17.5 inches

*Measurement taken from centre to centre of bolt slot/hole

• Measurement taken from base to top edge of arm

¶ Measurement taken from edge of spool to edge of hose guide rollers

