



GRACO XDV20 SERIES CONTROL VALVE

For standard and heavy-duty applications, both indoor and outdoor, the XDV20 control valves are designed to perform in larger dealerships with longer plumbing runs and greater fluid usage. The control valve is compatible with a wide range of nozzles and fluid extensions and is capable of pumping oil up to 75.7 lpm (20 gpm).

High-flow, non-metered oil dispense for Automotive dealerships, Heavy-duty dealerships, Fast lube centers, Fleet service facilities, In-plant, Lube trucks, and Mining.

SPECIFICATIONS:

Compatible Material	Oil, Antifreeze
Dispense Type	Manual
Extension Type	Rigid
Includes	Nozzle, Extension
Inlet Size (in / mm)	3/4 / 19.05
Inlet Thread Gender	Female
Inlet Thread Type	NPT
Maximum Operating Temperature (°C)	82
Maximum Working Pressure (bar / kPa)	#103.4 / 10340
Minimum Operating Temperature (°C)	-40
Model	XDV20
Outlet Size (in / mm)	7/8 / 22.225
Outlet Thread Gender	Female
Outlet Thread Type	Straight Thread O-Ring
Recommended Environment	Indoor, Outdoor
Trigger Lock	Locking
Type	Non-Metered Dispense Valve
Weight (kg)	0.18
Wetted Material	Aluminium, Stainless Steel, CS, Acetal, Nitrile Rubber, TPE



FEATURES & BENEFITS:

- Lock-on/Lock-off trigger allows hands free operation
- Sturdy cast body designed for use in tough environments
- Inlet 3/4 in. NPT with swivel
- Features rigid extension with high flow nozzle

PART NO.

AF-G-247722

GRACO XDV20 3/4" NPT Swivel Inlet, Rigid Extension