



FARM REFUELLERS

SINGLE SKIN DIESEL STORAGE TANK



FEATURES & BENEFITS:

- Heavy duty 6mm steel single skin tank
- Complete with 2" fill point camlock ball valve, check valve and Calibrated dipstick
- Lifting lugs on tank
- Heavy duty front step fitted to front of the tank for access to dip point
- Tanks are UL142 certified
- Designed to provide a cost effective solution to replace overhead diesel tanks in the agricultural industry

APPLICATIONS:

- Agriculture

SPECIFICATIONS

PART NO.	MAX CAPACITY (L)	DIMENSIONS (MM)	WEIGHT (KG)
AF-FRT-9.0	9,130	2,600 (L) x 2,200 (W) x 2,480 (H)	1,250
AF-FRT-18.0	18,250	5,760 (L) x 2,200 (W) x 2,480 (H)	1,700

* GA drawings available on request

PUMPING OPTIONS

- 12V Bi Pump Kit 80 LPM with 4m Hose, Mechanical Meter, Auto Nozzle and 10 Micron Bulk Fuel Filter with Breather
- 240V Bowser 70 LPM with 4m Hose, Mechanical Meter, Auto Nozzle and 10 Micron Bulk Fuel Filter with Breather
- 240V Fuel Management Bowser 70 LPM with 4m Hose, Software Kit, USB Key Reader, Managers Key, 10 User Keys, Auto Nozzle and 10 Micron Bulk Fuel Filter with Breather