



ULTRAFLO 100 BOWSER WITHOUT PEDESTAL

FEATURES & BENEFITS:

- **All-in-one refueling unit** - Everything needed for fuel transfer in a single package, with no separate sourcing
- **Built-in nozzle holster with automatic pump stop** - Pump shuts off when the nozzle is returned, improving safety and preventing accidental run-on
- **Self-priming vane pump** - Reliable start-up and consistent delivery without manual priming
- **Wall-mount as standard** - Space-saving installation; pedestal available as an option

SPECIFICATIONS:

Pump type	Self-priming rotary vane
Pump body	Cast Iron
Power supply	240 V AC
Maximum flow rate	Up to 100 L/min - 26,42 GPM
Max pressure	2,5 bar / 36 psi
Duty cycle	S2 30 min
Inlet/Outlet	1" F / 1" F BSP/G
Flow meter	4-digit mechanical/display meter
Delivery hose	4 m length, 1" (25 mm) ID
IP Rating	IP55
Nozzle	Automatic shut-off nozzle
Nozzle storage	Integrated holster with automatic pump stop
Compatible fluids	Diesel Only
Mounting	Wall mount (standard)
Gross weight	29 kg



PART NO.

AF-E-AF3000	ULTRAFLO Cabinet Pump - 100 LPM
AF-E-AF100000L	ULTRAFLO Bowser Pedestal