



ULTRAFLO DUAL HEAD ASSEMBLY



The ULTRAFLO Head Assembly is a high-performance component designed for bulk fluid filtration systems. This product is part of Bulk Filtration and is engineered for durability and efficiency in fluid handling applications.

SPECIFICATIONS:

Inlet Size	1 1/2 SAE 4 Bolt Code 61
Outlet Size	1 1/2 SAE 4 Bolt Code 61
Connection	1&1/2" SAE 4-Bolt Code 61 Flange
Filter Quantity	2
Max. Flow Range	125 gpm / 473 lpm
Fluid Compatibility	All diesel fuels and lubricants
Working Pressure	350 psi / 2413 kPa / 24.1 bar

Rated Static Burst	800 psi / 5520 kPa / 55.2 bar
Operating Temperature	40 to 245 F / -40 to 118 C
Indicator Port	Use to adapt pressure gauges or sampling ports (sold separately)
Construction	Aluminum head with threaded steel inserts and Viton seals
Dimensions	32x13x18
Weight	4 Kg

COMPATIBLE FILTERS

AF-UF-DBB8664	25UM@BETA 2000 - Engine Oil and Gear Oil (P568664)
AF-UF-DBB8665	7UM@BETA 2000 - Transmission Oil & Hydraulic Oil UF-P568665
AF-UF-DBB8666	All Fuels 4 micron@Beta 2000 (P568666)
AF-UF-DBB0248	Water Absorbing Media For Ethanol - Free Fluids (P570248)
AF-UF-DBB8777	CFLS Spin-On Element 7UMDERT

PART NO.

AF-UF-P568583	ULTRAFLO 1 1/2" SAE 4 Bolt (Dual Head) - 473 LPM Max Flow
---------------	---