



FLUIDLINK[®]

WIRELESS READER (WAND)

The Fluidlink Wireless Wand provides a secure, wireless solution for pump activation using RFID or AVI tags for users and assets. It offers configurable modes for two pumps with profile-based pump selection, featuring a convenient wireless charging dock and a return-to-home LED and buzzer for easy operation.

APPLICATIONS:

- Primary industries
- Infrastructure industries
- Service Sector
- Industrial Sector

SPECIFICATION:

Supply Voltage:

12VDC

Operating Temperature Range:

-25°C to 65°C

Humidity Range:

95% non-condensing

Ingress Protection Rating (IP):

IP56

FEATURES & BENEFITS:

- Allows secure pump activation using RFID or AVI tags for users and assets
- Configurable for two pumps with profile-based pump selection
- Includes Qi wireless charging dock for convenient recharging
- Equipped with LED and buzzer for return-to-home alerts
- Easy to set up and adaptable to various operational environments
- IP65 waterproof for protection against dust and water
- Durable UHMWPE body for high impact resistance
- Robust stainless-steel handle for added durability
- Stainless steel, glove-compatible buttons for ease of use
- High-brightness operational LEDs to clearly indicate status and functionality

PART NO.

AF-FL-826659	FLUIDLINK Wireless Reader for RFID/BLE IDs (WAND)
AF-FL-570663	FLUIDLINK Wireless Reader (WAND) Charging Dock