



A-FLO CLEAR CAPTOR FILTER 5 MICRON

The CLEAR CAPTOR is a cartridge-filter system designed for suction or delivery flow of fuels. It features a high-performance replaceable cartridge and a transparent plastic container that captures both water and particulate contaminants, enabling quick safe drainage via a bottom valve ensuring longer filter life.

FEATURES & BENEFITS:

- Replaceable cartridge: economical servicing and minimal downtime.
- High efficiency filtration: captures fine particles (e.g., $\beta 2/5 \mu\text{m}$ rating).
- Compact size: suitable for both mobile and stationary installations.
- Flow versatility: can be installed in suction or delivery lines.
- Transparent bowl & drain valve: visual monitoring of collected contaminants plus safe and easy removal.
- Durable, service-friendly design: lower maintenance overhead and longer equipment life.



SPECIFICATIONS:

Flow Rate Range	100 L/min
Inlet/Outlet Connection	1" BSP
Filtering Efficiency	$\beta 2 / 5 \mu\text{m}$
Maximum Operating Pressure	5 bar
Weight:	approx 2.3kg
Packaging Dimension	approx 390 × 285 × 140 mm
Pressure Drop	<0.5 bar (SAE10W oil at 20°C)
Operating Temperature	-10°C to +50°C

PART NO.

AF-FP-611B00

A-FLO Clear Captor Filter 5 Micron